


不锈钢圆锥滚子轴承

Stainless steel tapered roller bearings



内径15~70mm

Bore diameter 15~70mm



不锈钢材料	Material
stainless steel	420 440 304 316

轴承型号 Bearing NO.	外形尺寸 (mm) Boundary dimension(mm)					r1(min)	重量 Weight Kg
	d	D	T	B	C		
SS30202	15	35	11.75	11	10	1	0.096
SS30302		42	14.25	13	11	1	0.098
SS30203		40	13.25	12	11	1	0.080
SS30303	17	47	15.25	14	12	1	0.134
SS32203		40	17.25	16	14	1	0.102
SS30204	20	47	15.25	14	12	1	0.127
SS30304		52	16.25	15	13	1.5	0.169
SS32004		42	15	15	12	0.6	0.097
SS32204		47	19.25	18	15	1	0.160
SS30205	25	52	16.25	15	13	1	0.154
SS30305		62	18.25	17	15	1.5	0.272
SS32005		47	15	15	11.5	0.6	0.114
SS32205		52	19.25	18	16	1	0.187
SS30206	30	62	17.25	16	14	1	0.241
SS30306		72	20.75	19	16	1.5	0.408
SS32006		55	17	17	13	1	0.166
SS32206		62	21.25	20	17	1	0.301
SS30207	35	72	18.25	17	15	1.5	0.344
SS30307		80	22.75	21	18	2	0.540
SS32007		62	18	18	14	1	0.224
SS32207	40	72	24.25	23	19	1.5	0.457
SS30208		80	19.75	18	16	1.5	0.435
SS30308		90	25.25	23	20	2	0.769
SS32008		68	19	19	14.5	1	0.273
SS32208	45	80	24.75	23	19	1.5	0.558
SS30209		85	20.75	19	16	1.5	0.495
SS30309		100	27.25	25	22	2	1.010
SS32009		75	20	20	15.5	1	0.346
SS32209	50	85	24.75	23	19	1.5	0.607
SS30210		90	21.75	20	17	1.5	0.563
SS30310		110	29.25	27	23	2.5	1.310
SS32010		80	20	20	15.5	1	0.366
SS32210	55	90	24.75	23	19	1.5	0.648
SS30211		100	22.75	21	18	2	0.740
SS30311		120	31.5	29	25	2.5	1.660
SS32011		90	23	23	17.5	1.5	0.563
SS32211	60	100	26.75	25	21	2	0.876
SS30212		110	23.75	22	19	2	0.949
SS30312		130	33.5	31	26	3	2.060
SS32012		95	23	23	17.5	1.5	0.576
SS32212	65	110	29.75	28	24	2	1.18
SS30213		120	24.75	23	20	2	1.180
SS30313		140	36	33	28	3	2.550
SS32013		100	23	23	17.5	1.5	0.63
SS32213	70	120	32.75	31	27	2	1.58
SS30214		125	26.25	24	21	2	1.260
SS30314		150	38	35	30	3	3.060
SS32014		110	25	25	19	1.5	0.848
SS32214		125	33.25	31	27	2	1.68


不锈钢圆锥滚子轴承

Stainless steel tapered roller bearings



内径75~150mm

Bore diameter 75~150mm



不锈钢材料	Material
stainless steel	420 440 304 316

轴承型号 Bearing NO.	外形尺寸 (mm) Boundary dimension(mm)					r1(min)	重量 Weight Kg
	d	D	T	B	C		
SS30215	75	130	27.25	25	22	2	1.410
SS30315		160	40	37	31	3	3.570
SS32015		115	25	25	19	1.5	0.909
SS32215	80	130	33.25	31	27	2	1.74
SS30216		140	28.25	26	22	2	1.720
SS30316		170	42.5	39	33	3	4.410
SS32016	85	125	29	29	22	1.5	1.28
SS32216		140	35.25	33	28	2.5	2.18
SS30217		150	30.5	28	24	2	2.140
SS30317	90	180	44.5	41	34	4	5.200
SS32017		130	29	29	22	1.5	1.35
SS32217		150	38.5	36	30	2.5	2.75
SS30218	95	160	32.5	30	26	2.5	2.660
SS30318		190	46.5	43	36	4	6.030
SS32018		140	32	32	24	2	2.18
SS32218	100	160	42.5	40	34	2.5	3.49
SS30219		170	34.5	32	27	3	3.070
SS30319		200	49.5	45	38	3	6.580
SS32019	105	145	32	32	24	2	1.83
SS32219		170	45.5	43	37	3	4.3
SS30220		180	37	34	29	3	3.780
SS30320	110	215	51.5	47	39	4	8.560
SS32020		150	32	32	24	2	1.91
SS32220		180	49	46	39	3	5.12
SS30221	120	190	39	36	30	3	4.390
SS30321		225	53.5	49	41	4	9.790
SS32021		160	35	35	26	2.5	2.42
SS32221	130	190	53	50	43	3	6.25
SS30222		200	41	38	32	3	5.180
SS30322		240	54.5	50	42	4	11.400
SS32022	140	170	38	38	29	2.5	3.07
SS32222		200	56	53	46	3	7.43
SS30224		215	43.5	40	34	3	6.230
SS30324	150	260	59.5	55	46	4	14.200
SS32024		180	38	38	29	2.5	3.25
SS32224		215	61.5	58	50	3	9.08
SS30226	140	230	43.75	40	34	4	7.250
SS30326		280	63.75	58	49	5	17.400
SS32026		200	45	45	34	2.5	4.96
SS32226	150	230	67.75	64	54	3	11.2
SS30228		250	45.75	42	36	4	9.260
SS30328		300	67.75	61	53	5	21.200
SS32028	150	210	45	45	34	2.5	5.28
SS32228		250	71.75	68	58	4	14.1
SS30230		270	49	45	38	4	11.200
SS30330	150	320	72	65	55	5	25.500
SS32030		225	48	48	36	3	6.37
SS32230		270	77	73	60	4	18.2