

滚针轴承  
needle bearing

STPM®

NART...UU

NART...UUR

内径5~50mm

Bore diameter 5~50mm



轴承型号 Bearing NO.	外形尺寸(mm) Boundary dimensions(mm)						基本额定负荷 Basic Load Rating		极限转速 Limiting
	d	D	B	C	d1	rs	动 Dynamic	静 Static	Speed
	mm					min	N		rpm
NART5	5	16	12	11	12	0.15	3800	3750	22000
NART6	6	19	12	11	14	0.15	4250	4600	20000
NART8	8	24	15	14	19	0.3	6800	7700	15000
NART10	10	30	15	14	23	0.6	8100	9700	11000
NART12	12	32	15	14	25	0.6	8700	11000	9000
NART15	15	35	19	18	27	0.6	12900	19000	7000
NART17	17	40	21	20	32	1	14200	20400	6000
NART20	20	47	25	24	37	1	19500	32000	4900
NART25	25	52	25	24	42	1	21200	38000	3600
NART30	30	62	29	28	51	1	34000	59000	2600
NART35	35	72	29	28	58	1.1	37000	69000	2000
NART40	40	80	32	30	66	1.1	49000	94000	1700
NART45	45	85	32	30	72	1.1	51000	101000	1500
NART50	50	90	32	30	76	1.1	52000	108000	1300